

What It Takes To Be
“Thaler or Equal”

When specifications read Thaler or Equal, it is incumbent upon specifiers and building owners to determine what it means to be “Or Equal”. The following data has been presented to quickly help assess the comparative merits of “competitive” products. Thaler STACK JACK™ flashing products have a number of *Value Added* features that should be considered when trying to equate the “Or Equal”.

**Check “The
Competition”****Thaler *Value
Added* Features**

- | | |
|--------------------------|--|
| <input type="checkbox"/> | <input checked="" type="checkbox"/> EPDM Triple Pressure Grommet Seal; EPDM “memory” in the seal provides constant pressure to outside of vent pipe to prevent leaks. See Thaler EPDM Flashing Seals literature. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> EPDM Base Seal; EPDM “memory” in the seal provides constant pressure to outside of vent pipe to prevent condensation build-up. See Thaler EPDM Flashing Seals literature. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Incorporates air barrier principles; meets the requirements for air leakage control better than any vent stack flashing on the market today. See Thaler EPDM Flashing Seals literature. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> EPDM Triple Pressure Grommet Seal and Base Seal sizes; available for 2”, 3”, 4”, 5” and 6” (51, 76, 102, 127 and 152 mm) diameter vent stacks. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Injection molded urethane insulation (where applicable); adheres to inner side of sleeve without air pockets. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> One piece, spun aluminum flashing sizes; supplied in a variety of diameters and heights for plastic, steel, stainless, copper or cast iron vent pipes e.g. 2”, 3”, 4”, 5” and 6” (51, 76, 102, 127 and 152 mm) diameters, and 7”, 13” and 19” (178, 330 and 483 mm) standard heights. Other sizes available upon request. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Treated deck flange; can be PVC coated for proper adhesion of PVC membrane or bituminous painted for BUR or ModBit membrane. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Material options and thickness; available in .064” (1.6 mm) mill finish 1000-0T alloy aluminum, .032” (0.831 mm) 24 oz. copper or .031” (0.79 mm) 22 ga. Type 304 stainless steel. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> CSA Approved; All Thaler STACK JACK flashings conform to CSA B272-93 - Prefabricated Self-Sealing Roof Vent Flashings. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> 20 year Warranty; guaranteed against leaks, condensation and defects in materials and/or manufacture when installed in accordance with Thaler “Installation Instructions”. |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Maintenance-Free; never needs caulking (any caulking at any time will invalidate 20 year warranty) |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> Written “Installation Instructions”; provided with every Thaler product. |