




MERS-625A RE-ROOFING ALUMINUM PIPE SUPPORT (Double Plain Pipe)

PATENTED

INSTALLATION

"Installation Instructions" are provided with every Thaler product. Essentially, the Thaler MERS-625A Pipe Support is installed at required centres by fastening the aluminum mounting plate to the structural roof deck, placing the flashing sleeve over the support and roof membrane, installing the stirrup-type pipe holder assemblies, and as follows:

BUR: Set flashing deck flange in layer of plastic cement and flash in with 3 overlapping layers of felt flashing.

ModBit: Torch membrane until bitumen is fluid and set flashing deck flange into fluid. Flash in flange with two overlapping layers of ModBit and seal with asphalt sealer. Do not overheat (melt) EPDM Base Seal.

Single Ply: Set flashing deck flange in layer of membrane adhesive and extend single ply up sleeve to highest elevation possible and clamp membrane to STACK JACK Flashing. Note: for PVC membrane, specify PVC coated aluminum, etc. STACK JACK by adding the suffix P to the end of the model number, e.g. MERS-625A-A-P; weld roofing to deck flange using PVC torch.

Precautions: Apply an asphaltic or other type protective coating to aluminum STACK JACK Flashing to a height of 2" (51 mm) above a limestone ballast to avoid corrosive reaction. Also, if coating deck flange with bituminous paint on site, allow 24 hours for drying before applying roof membrane.

Pipe Holder Assemblies: Thread hollow aluminum upper support onto lower support leg to exact elevation required and install stirrup-type pipe holders.

Ordering and Availability: Specify flashing material required by adding appropriate suffix to model number e.g. MERS-625A-A, for aluminum, etc. Available throughout North America. Contact Thaler for list of distributors and current cost information. Most products are readily available from stock.

ROOF SPECIALTIES

MERS-625A RE-ROOFING ALUMINUM PIPE SUPPORT (Double Plain Pipe)

DESCRIPTION

Thaler MERS-625A Pipe Support consists of a round, urethane insulated, hollow section 6061-T6 aluminum support with threaded leg assembly for vertical adjustment and mounting plate, mounting hardware (adhesive type fasteners supplied by others), stirrup-type pipe holder, and stainless steel pipe roller assemblies. A urethane insulated STACK JACK flashing available in aluminum, copper, or stainless steel, with EPDM Triple Pressure Grommet Seal at the top of the flashing and EPDM Base Seal, completes the support.

Support Spacing: As per CAN1-B149.1-M86 for natural gas and propane. Spacing for pipes other than gas to be determined by mechanical or electrical engineer for safe loading.

Prominent Features: Threaded leg assembly provides up to 4" (102 mm) vertical adjustment. Light weight, strong-as-steel and non-corrosive. Maintenance free (EPDM flashing seals never need caulking. See Thaler EPDM Flashing Seals literature).

Options: See Section A of manual for STACK JACK Flashings options.

RECOMMENDED USE

Suitable for all flat roofs as a double, plain (uninsulated) pipe support for pipe sizes from 2" (51 mm) to 4" (102 mm) diameter. Ultimate bearing load is 7350 lbs. (3334 kg) per leg; apply appropriate safety factor.

WARRANTY

20 year warranty against leaks, condensation and defects in materials and/or manufacture when installed in accordance with Thaler "Installation Instructions". Copy of Warranty Certificate available upon request.

MAINTENANCE

No maintenance required (maintenance free).

SPECIFICATION (Short Form)

Re-roofing pipe supports (double plain pipe): Thaler MERS-625A adjustable height 6061-T6 hollow aluminum with mill finish, urethane insulated supports, 2" (51 mm) dia., with appropriate hardware (adhesive type supplied by others), for fastening to structural roof deck, stirrup-type pipe holders, and Type 304 stainless steel pipe roller assemblies sized to suit [] actual O.D. pipe; [SJ-34 non-insulated New Standard STACK JACK flashing for concrete deck.] [SJ-37 pre-insulated New Standard STACK JACK flashing for steel deck.] 7" (178 mm) high, consisting of [.064" (1.6 mm) mill finish 1100-OT alloy aluminum] [.032" (0.831 mm) 24 oz. copper] [.031" (0.79 mm) 22 ga. Type 304 stainless steel], 2" (51 mm) dia. to CSA B272-93; with EPDM Triple Pressure Grommet Seal and EPDM Base Seal and [PVC coated deck flange] [bituminous painted deck flange]; manufactured by Thaler Metal Industries, 1-800-387-7217 (Mississauga, Ontario, Canada) or 1-800-576-1200 (New Braunfels, TX), installed as per manufacturer's written instructions. Provide 20 year warranty against leaks, condensation and defects in materials and/or manufacture.